

Specifications

Specification	Value
No./teeth	10 qty
Power	3.2 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	105 mm
No./mount. holes with thread [qty.]	0 qty
C.1 [mm]	10.50 mm
L.1 [mm]	272 mm
Voltage	12 V
Rotation	CW
C.2 [mm]	10.50 mm
Size A [mm]	82 mm
Size B [mm]	35 mm

Applications

Make	Vehicle
JOHN	DEERE

Original Code

AZF4655[	IS1027
RE19196	

Equivalent Code (Vehicle Manufacturer)

273-32104 (DIXIE)	TS-6265 (DIXIE)
6040246 (SANDO)	630.505.102 (PSH)
630.537.102 (PSH)	630.537.102.030 (PSH)
630.537.102.500 (PSH)	630.538.102 (PSH)
630.538.102.460 (PSH)	S134.180 (PSH)
S134.181 (PSH)	S144.176 (PSH)
S144.177 (PSH)	72735921 (MAHLE)
MS 293 (MAHLE)	MS293A (MAHLE)
AJ59342 (JOHN DEERE)	RE19196 (JOHN DEERE)
RE19275 (JOHN DEERE)	RE41799 (JOHN DEERE)
RE42730 (JOHN DEERE)	RE49033 (JOHN DEERE)
RE501693 (JOHN DEERE)	RE505746 (JOHN DEERE)
RE509658 (JOHN DEERE)	RE516157 (JOHN DEERE)
RE51694 (JOHN DEERE)	RE529594 (JOHN DEERE)
RE533976 (JOHN DEERE)	RE54092 (JOHN DEERE)
RE551445 (JOHN DEERE)	RE59590 (JOHN DEERE)
RE62916 (JOHN DEERE)	RE68470 (JOHN DEERE)
SE501400 (JOHN DEERE)	SE501402 (JOHN DEERE)
SE501425 (JOHN DEERE)	SE501428 (JOHN DEERE)
SE501852 (JOHN DEERE)	TY24305 (JOHN DEERE)
TY24438 (JOHN DEERE)	TY25971 (JOHN DEERE)
TY34438 (JOHN DEERE)	TY6688 (JOHN DEERE)
TY6719 (JOHN DEERE)	CST40246 (CASCO)
CST40246AS (CASCO)	CST40246ES (CASCO)
CST40246GS (CASCO)	CST40246OS (CASCO)
CST40246RS (CASCO)	DRS0303 (DELCO)
MAHMS293 (WOODAUTO)	MAV123600 (SIOM)
MAV172060 (SIOM)	MAV421720 (SIOM)
MAV422460 (SIOM)	STI4603 (KRAUF)
S9325S (AS-PL)	UD105194S (AS-PL)
UD14889S (AS-PL)	S12ML0709 (SIDAT)
S12ML0709A2 (SIDAT)	ANM12523X (ANDEL)
STR79146 (ELECTROLOG)	STR7958 (ELECTROLOG)
STX200520 (STARDAX)	STX200520R (STARDAX)
STX200819 (STARDAX)	