



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	351 mm
Rotation	CW
Size A [mm]	88.5 mm
Size B [mm]	29.5 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	127 mm
Insulated return	Yes
O.2 [mm]	90 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Applications

Make
CATERPILLAR

Original Code

3704009	AZF4103
IS1129	

Equivalent Code (Vehicle Manufacturer)

UD21477S (AS-PL)	256041M (KUHNER)
640.551.103.090 (PSH)	640.551.103.311 (PSH)
S143.441 (PSH)	S144.488 (PSH)
CST21246AS (CASCO)	CST21246GS (CASCO)
109472 (FARCOM)	72735747 (MAHLE)
MS119 (MAHLE)	N37636 (PERKINS)
3704009 (CATERPILLAR)	N40982 (CATERPILLAR)
WG2044878 (WILMINK GROUP)	20419642BN (REAL)
20419642OE (REAL)	6021246.0 (SANDO)
6021246.1 (SANDO)	LETIS1129 (WOODAUTO)
MAHMS119 (WOODAUTO)	STR60651 (WOODAUTO)
182-30506 (ROBERT'S)	UNIT BOM 182-1150 (WAI / TRANSP0)