



Specifications

Specification	Value
No./mount. holes [qty.]	4 qty
O.1 [mm]	124 mm
No./mount. holes with thread [qty.]	1 qty
L.1 [mm]	322 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	47 mm
No./teeth	10 qty
No./teeth (fits into) [qty.]	10 qty
C.4 [mm]	11.00 mm
Power	4.2 kW
O.4 [mm]	90 mm
O.3 [mm]	90 mm
O.2 [mm]	30.5 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	M12x1.75 mm

Applications

Make	Vehicle
JOHN	DEERE

Original Code

AZF4597	IS1063
RE105298	

Equivalent Code (Vehicle Manufacturer)

0001362324 (BOSCH)	10-14194S (WHITE)
30-3123383 (WHITE)	10461450 (DELCO)
10461451 (DELCO)	10465049 (DELCO)
10465050 (DELCO)	1107866 (DELCO)
1109198 (DELCO)	1109263 (DELCO)
1113281 (DELCO)	1113282 (DELCO)
12301341 (DELCO)	1998330 (DELCO)
323-674 (DELCO)	323-684 (DELCO)
323442 (DELCO)	323443 (DELCO)
113454 (CARGO)	F032113454 (CARGO)
18195 (LESTER)	4274 (LESTER)
182-30104 (ROBERT'S)	18483N (WAI / TRANSPO)
1903103M91 (MASSEY FERGUSON)	1903117M91 (MASSEY FERGUSON)
517533M93 (MASSEY FERGUSON)	579937M91 (MASSEY FERGUSON)
228000-6400 (DENSO)	254669 (KUHNER)
260-23120 (DIXIE)	3185C37G01 (THERMO KING)
347198 (MERCURY)	646218 (MERCURY)
35259630 (PRESTOLITE)	S5011L (PRESTOLITE)
450732R91 (CASE)	596493R92 (CASE)
6010343.0 (SANDO)	6651258 (BOBCAT)
6651664 (BOBCAT)	91-01-4310 (WILSON)
91-23-6508 (WILSON)	910886 (CLARK)
CGB-1633 (AINDE)	CGB-23818 (AINDE)
CST10343AS (CASCO)	LETIS1063 (WOODAUTO)
STR60621 (WOODAUTO)	MAV122280 (SIOM)
MAV123430 (SIOM)	MS 94 (MAHLE)
MS94A (MAHLE)	RE105298 (JOHN DEERE)
RE501766 (JOHN DEERE)	RE501767 (JOHN DEERE)
RE505744 (JOHN DEERE)	RE507639 (JOHN DEERE)
RE508322 (JOHN DEERE)	RE509903 (JOHN DEERE)
RE540136 (JOHN DEERE)	RE60171 (JOHN DEERE)
RE60239 (JOHN DEERE)	RE70728 (JOHN DEERE)
SE501850 (JOHN DEERE)	SE502631 (JOHN DEERE)
STRF223 (3EFFE)	STRS640 (3EFFE)
S9070 (AS-PL)	UD11315S (AS-PL)
332072 (LOGISTIK)	STR7930 (ELECTROLOG)
STX200383 (STARDAX)	STX200904 (STARDAX)
STX201006 (STARDAX)	STX201072 (STARDAX)