



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	350 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	30 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	90 mm
O.2 [mm]	127 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Applications

Make
PERKINS

Original Code

2873K601	AZF4275
IS1193	

Equivalent Code (Vehicle Manufacturer)

115389 (CARGO)	F032115389 (CARGO)
182-30168 (ROBERT'S)	25-4462 (ELSTOCK)
260-23123 (DIXIE)	TS-6281 (DIXIE)
2873K601 (PERKINS)	2873K631 (PERKINS)
3586847 (PERKINS)	312-7576 (CATERPILLAR)
3127536 (CATERPILLAR)	3575204 (CATERPILLAR)
5300551 (CLAAS)	DRS0272 (DELCO)
DRS0272N (DELCO)	LRS03789 (LUCAS)
LRS3789 (LUCAS)	MAHMS400 (WOODAUTO)
MS 400 (MAHLE)	MS400A (MAHLE)
STRF216 (3EFFE)	S9287S (AS-PL)
UD13620S (AS-PL)	ANM12492X (ANDEL)
332260 (LOGISTIK)	CST21189AS (CASCO)
CST21189GS (CASCO)	20419981BN (REAL)
20419981OE (REAL)	6021189.0 (SANDO)
6021189.1 (SANDO)	STR78015 (ELECTROLOG)
STX210179 (STARDAX)	STX210179R (STARDAX)
700.523.103.090 (PSH)	700.523.103.311 (PSH)
S135.042 (PSH)	S145.811 (PSH)