



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	321 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	29 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	90 mm
O.2 [mm]	127 mm
C.1 [mm]	11.00 mm
Voltage	12 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Applications

Make	Vehicle
MASSEY	FERGUSON
PERKINS	

Original Code

2873A030	AZF4148
IS1160	IS1207

Equivalent Code (Vehicle Manufacturer)

S9199S (AS-PL)	UD16537S (AS-PL)
115393 (CARGO)	F032115393 (CARGO)
CST21207GS (CASCO)	714-29300R (JCB)
71429300 (JCB)	71429500 (JCB)
STI5393 (KRAUF)	255976M (KUHNER)
3551773M91 (LANDINI)	3648190M91 (LANDINI)
0009710184 (LINDE)	72735923 (MAHLE)
MS295 (MAHLE)	1447773R1 (MASSEY FERGUSON)
2873001T (MASSEY FERGUSON)	1446802M91 (PERKINS)
1447732M1 (PERKINS)	1447732R1 (PERKINS)
2873001 (PERKINS)	2873A102 (PERKINS)
2873B056 (PERKINS)	3581576M1 (PERKINS)
3581576R1 (PERKINS)	700.517.103.090 (PSH)
700.517.103.311 (PSH)	S134.735 (PSH)
S145.301 (PSH)	20419702OE (REAL)
182-30314 (ROBERT'S)	6021207.1 (SANDO)
MAHMS295 (WOODAUTO)	S12ML0301 (SIDAT)
S12ML0301A2 (SIDAT)	STR7864 (ELECTROLOG)
STX200542 (STARDAX)	STX200678 (STARDAX)
STX210086 (STARDAX)	