



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	128 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	350 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	29 mm
No./teeth	10 qty
Power	4.2 kW
O.3 [mm]	90 mm
O.2 [mm]	90 mm
C.1 [mm]	10.50 mm
Voltage	12 V
C.3 [mm]	10.50 mm
C.2 [mm]	10.50 mm

Applications

Make
PERKINS

Original Code

2873A031	30326
AZF4248	

Equivalent Code (Vehicle Manufacturer)

114852 (CARGO)	F032114852 (CARGO)
182-30175 (ROBERT'S)	204195510E (REAL)
25-4223 (ELSTOCK)	26925193A (PERKINS)
2873A031 (PERKINS)	2873K604 (PERKINS)
2873K605 (PERKINS)	2873K606 (PERKINS)
2873K635 (PERKINS)	3317010 (PERKINS)
6021155.1 (SANDO)	72736031 (MAHLE)
MS403 (MAHLE)	CST21155GS (CASCO)
DRS0277 (DELCO)	LETIS1202 (WOODAUTO)
MAHMS403 (WOODAUTO)	STR60650 (WOODAUTO)
LRS02551 (LUCAS)	LRS2551 (LUCAS)
MAV231550 (SIOM)	PRSL275 (3EFFE)
STRL275L (3EFFE)	S9235 (AS-PL)
UD11320S (AS-PL)	TS-6282 (DIXIE)
S12ML0292A2 (SIDAT)	ANM12497X (ANDEL)
STR79259 (ELECTROLOG)	30326N (WAI / TRANSPO)
7169479 (BOBCAT)	7220938 (BOBCAT)
STX200560 (STARDAX)	STX200678 (STARDAX)
STX210091 (STARDAX)	