



Specifications

Specification	Value
No./teeth	10 qty
Power	4 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	105 mm
No./mount. holes with thread [qty.]	0 qty
C.1 [mm]	13.50 mm
L.1 [mm]	322 mm
Voltage	24 V
Rotation	CW
C.2 [mm]	13.50 mm
Size A [mm]	82.5 mm
Size B [mm]	35 mm

Applications

Make	Vehicle
JOHN	DEERE

Original Code

6596	AZJ3326
IS1088	RE503118

Equivalent Code (Vehicle Manufacturer)

0-23000-2050 (NIKKO)	02-23-1041 (NIKKO)
0001368059 (BOSCH)	10461444 (DELCO)
1113272 (DELCO)	1998519 (DELCO)
120-30364 (ROBERT'S)	255200 (KUHNER)
260-67225 (DIXIE)	35259650 (PRESTOLITE)
S5007L (PRESTOLITE)	6010708 (SANDO)
631.001.102 (PSH)	631.504.102 (PSH)
S134.289 (PSH)	S134.356 (PSH)
S144.328 (PSH)	6596N (WAI / TRANSPO)
8477 (CEVAM)	91-01-4377 (WILSON)
CST10708 (CASCO)	CST10708AS (CASCO)
CST10708ES (CASCO)	CST10708GS (CASCO)
CST10708OS (CASCO)	CST10708RS (CASCO)
MAHMS96 (WOODAUTO)	STR20034 (WOODAUTO)
MAV123600 (SIOM)	MAV127080 (SIOM)
MS 96 (MAHLE)	RE503118 (JOHN DEERE)
RE51725 (JOHN DEERE)	RE52120 (JOHN DEERE)
RE52150 (JOHN DEERE)	RE522738 (JOHN DEERE)
RE525799 (JOHN DEERE)	RE67086 (JOHN DEERE)
SE502286 (JOHN DEERE)	TY24303 (JOHN DEERE)
STRJ314 (3EFFE)	STRJ675 (3EFFE)
STRL842 (3EFFE)	UD13626S (AS-PL)
STR10314 (ELECTROLOG)	