



Specifications

| Specification                         | Value    |
|---------------------------------------|----------|
| No./mount. holes [ qty. ]             | 3 qty    |
| O.1 [ mm ]                            | 90 mm    |
| No./mount. holes with thread [ qty. ] | 0 qty    |
| L.1 [ mm ]                            | 341 mm   |
| Rotation                              | CW       |
| Size A [ mm ]                         | 89 mm    |
| Size B [ mm ]                         | 29 mm    |
| No./teeth                             | 10 qty   |
| Power                                 | 4 kW     |
| O.3 [ mm ]                            | 90 mm    |
| Insulated return                      | Yes      |
| O.2 [ mm ]                            | 127 mm   |
| C.1 [ mm ]                            | 11.00 mm |
| Voltage                               | 24 V     |
| C.3 [ mm ]                            | 11.00 mm |
| C.2 [ mm ]                            | 11.00 mm |

Applications

| Make    |
|---------|
| PERKINS |

Original Code

|         |        |
|---------|--------|
| AZF4104 | N37637 |
| S1130   |        |

Equivalent Code (Vehicle Manufacturer)

|                      |                       |
|----------------------|-----------------------|
| 182-30410 (ROBERT'S) | 20419926OE (REAL)     |
| 255923M (KUHNER)     | 3704011 (CATERPILLAR) |
| N40983 (CATERPILLAR) | 6021629.1 (SANDO)     |
| 701.510.103 (PSH)    | 701.510.103.311 (PSH) |
| S135.411 (PSH)       | S145.525 (PSH)        |
| 72735727 (MAHLE)     | MS99 (MAHLE)          |
| CST21629GS (CASCO)   | MAV236290 (SIOM)      |
| N37637 (PERKINS)     | SG9137 (GHIBAUDI)     |
| UD20931S (AS-PL)     | WRM21629OE (WROOM)    |
| MAHMS99 (WOODAUTO)   | STR7931 (ELECTROLOG)  |