



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	90 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	348 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	30 mm
No./teeth	10 qty
Power	4 kW
O.3 [mm]	90 mm
O.2 [mm]	127 mm
C.1 [mm]	11.00 mm
Voltage	24 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Applications

Make	Vehicle	Model Types
VOGELE	1603-2	1004D-E44TA
VOGELE	1600-1	1104D-E44TA
VOGELE	1602-2	1104D-E44TA
VOGELE	1600-1 EP	1104D-E44TA
VOGELE	1800-1 EP	1106D-E66TA
VOGELE	1802-2	1106D-E66TA
VOGELE	1803-2	1106D-E66TA
VOGELE	1800-1	1106D-E66TA
VOGELE	1800-2 SJ	1106D-E66TA
VOGELE	1803-1	1106D-E66TA

Original Code (Vehicle Manufacturer)

182-1166	182-1166A
2010032	3575205
2873K406	3586846
T410862	5568664115
701.520.103	S135.255
S145.323	11.132.262
11.132.262 (ISKRA / LETRIKA)	AZF4266
AZF4266 (ISKRA / LETRIKA)	AZF4347
AZF4347 (ISKRA / LETRIKA)	IS1316
IS1316 (ISKRA / LETRIKA)	MS 130
S9351S	UD11324S
CST21640AS	CST21640GS
20419046BN	20419046OE
6021640.0	6021640.1
MAV236400A	STR79322

Equivalent Code (Vehicle Manufacturer)

182-1166 (WAI / TRANSP0)	182-1166A (WAI / TRANSP0)
2010032 (VOGELE)	3575205 (CATERPILLAR)
2873K406 (PERKINS)	3586846 (PERKINS)
T410862 (PERKINS)	5568664115 (TEREX)
701.520.103 (PSH)	S135.255 (PSH)
S145.323 (PSH)	MS 130 (MAHLE)
S9351S (AS-PL)	UD11324S (AS-PL)
CST21640AS (CASCO)	CST21640GS (CASCO)
20419046BN (REAL)	20419046OE (REAL)
6021640.0 (SANDO)	6021640.1 (SANDO)
MAV236400A (SIOM)	STR79322 (ELECTROLOG)