



Specifications

Specification	Value
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	341 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	47 mm
No./teeth	10 qty
Power	4 kW
O.3 [mm]	90 mm
Insulated return	Yes
O.2 [mm]	90 mm
C.1 [mm]	11.00 mm
Voltage	24 V
C.3 [mm]	11.00 mm
C.2 [mm]	11.00 mm

Applications

Make	Vehicle
JOHN	DEERE

Original Code

AZF4593	IS1117
RE522334	

Equivalent Code (Vehicle Manufacturer)

011912354 (CUMMINS)	01912354 (CUMMINS)
204192160E (REAL)	273-42205 (DIXIE)
TS-6263 (DIXIE)	45-4030 (ELSTOCK)
6021612.1 (SANDO)	72735793 (MAHLE)
MS 165 (MAHLE)	MS 627 (MAHLE)
88214719 (POWERMAX)	CST21612GS (CASCO)
LRS02358 (LUCAS)	LRS2358 (LUCAS)
RE522334 (JOHN DEERE)	SE502733 (JOHN DEERE)
S5012L (PRESTOLITE)	STI4593 (KRAUF)
STRF326 (3EFFE)	UD16546S (AS-PL)
STR79162 (ELECTROLOG)	STR7967 (ELECTROLOG)