



Specifications

| Specification                         | Value    |
|---------------------------------------|----------|
| No./mount. holes [ qty. ]             | 3 qty    |
| O.1 [ mm ]                            | 89 mm    |
| No./mount. holes with thread [ qty. ] | 0 qty    |
| L.1 [ mm ]                            | 239 mm   |
| Rotation                              | CW       |
| Size A [ mm ]                         | 89 mm    |
| Size B [ mm ]                         | 31 mm    |
| No./teeth                             | 10 qty   |
| No./teeth (fits into) [ qty. ]        | 10 qty   |
| Power                                 | 2.7 kW   |
| O.3 [ mm ]                            | 126 mm   |
| O.2 [ mm ]                            | 89 mm    |
| C.1 [ mm ]                            | 11.50 mm |
| Voltage                               | 12 V     |
| C.3 [ mm ]                            | 11.50 mm |
| C.2 [ mm ]                            | 11.50 mm |

Applications

| Make    |
|---------|
| PERKINS |

Original Code

|          |          |
|----------|----------|
| 2873A102 | 54293284 |
| 9142720  |          |

Equivalent Code (Vehicle Manufacturer)

|                            |                          |
|----------------------------|--------------------------|
| 20500968 (PRESTOLITE)      | 2873A102 (PERKINS)       |
| 3648190M92 (LANDINI)       | 42263570 (HERTH+BUSS)    |
| 54293284 (MAGNETI MARELLI) | CGB-23287 (AINDE)        |
| CGB-23289 (AINDE)          | IS0875 (ISKRA / LETRIKA) |
| MAV3610 (SIOM)             | MS 307 (MAHLE)           |
| STRX013 (ELECTROLOG)       | STX200542 (STARDAX)      |
| STX210086 (STARDAX)        | S9051 (AS-PL)            |