



产品规格

规格	参数值
No./teeth	10 qty
Power	1.4 kW
No./mount. holes [qty.]	2 qty
O.1 [mm]	99 mm
No./mount. holes with thread [qty.]	0 qty
C.1 [mm]	15.50 mm
L.1 [mm]	220 mm
Voltage	12 V
Rotation	CW
C.2 [mm]	12.00 mm
Size A [mm]	71 mm
Size B [mm]	23 mm

适用车型

品牌
CHRYSLER

原厂编码

17785	228000-7420
228000-7421	

替代编码 (汽车制造商)

17785N (WAI / TRANSP0)	17785R (WAI / TRANSP0)
PRSE227 (3EFFE)	STRE227 (3EFFE)
336-1722 (DELCO)	3371110 (DELCO)
113120 (CARGO)	F032113120 (CARGO)
3755259 (CHRYSLER)	5602-7702-AB (CHRYSLER)
5602-7702-AC (CHRYSLER)	5602-7702-AC2 (CHRYSLER)
5602-7702-AD (CHRYSLER)	5602-7702-AE (CHRYSLER)
5602-8210 (CHRYSLER)	R602-7702-AC (CHRYSLER)
SX3780 (DELPHI)	246-15125 (DIXIE)
S-8751 (DIXIE)	830.556.102.050 (PSH)
S135.442 (PSH)	STN3120 (KRAUF)
91-29-5444 (WILSON)	91-29-5444N (WILSON)
STR70180 (WOODAUTO)	UD21112S (AS-PL)
CST40340AS (CASCO)	60403400 (SANDO)
STR6308 (ELECTROLOG)	STX200375 (STARDAX)
STX201216 (STARDAX)	STX201216R (STARDAX)