



产品规格

规格	参数值
No./mount. holes [qty.]	3 qty
O.1 [mm]	127 mm
No./mount. holes with thread [qty.]	0 qty
L.1 [mm]	288 mm
Rotation	CW
Size A [mm]	89 mm
Size B [mm]	28 mm
No./teeth	12 qty
Power	5 kW
O.3 [mm]	93 mm
O.2 [mm]	81 mm
C.1 [mm]	10.50 mm
Voltage	24 V
C.3 [mm]	10.50 mm
C.2 [mm]	10.50 mm

适用车型

品牌
MAN

原厂编码

30291	51262017263
M008T63271	M8T63271

替代编码 (汽车制造商)

MITM8T63271 (WOODAUTO)	PREM85R3005SE (WOODAUTO)
STR71352 (WOODAUTO)	255470 (KUHNER)
255470M (KUHNER)	551.548.123.130 (PSH)
551.548.123.136 (PSH)	551.548.123.138 (PSH)
551.548.123.370 (PSH)	S133.534 (PSH)
S145.052 (PSH)	CST35657AS (CASCO)
CST35657GS (CASCO)	45-5334 (ELSTOCK)
51262017263 (MAN)	LRS04171 (LUCAS)
LRS4171 (LUCAS)	11.139.219 (ISKRA / LETRIKA)
AZE4710 (ISKRA / LETRIKA)	IS9517 (ISKRA / LETRIKA)
72524874 (MAHLE)	MS1035 (MAHLE)
M85405 (PRESTOLITE)	M85R3005SE (PRESTOLITE)
30291N (WAI / TRANSP0)	8067 (CEVAM)
336563 (LOGISTIK)	20437756BN (REAL)
20437756OE (REAL)	6035657.0 (SANDO)
6035657.1 (SANDO)	PRSF355 (3EFFE)
STRF355 (3EFFE)	STM7123 (KRAUF)
CGB-21044 (AINDE)	DRS1044 (DELCO)
S5239S (AS-PL)	UD13180S (AS-PL)
UD19642S (AS-PL)	STR5464 (ELECTROLOG)